



WEATHER-MASTER S/T²

T/S-Speed Rated
Studdable

CALL TODAY FOR MORE INFORMATION

847-395-2345



High Traction Tread Design

The intricate tread pattern balances winter traction and a smooth, quiet ride. The deep lateral and notched circumferential grooves provide excellent evacuation of water and slush from the tread contact patch.

Patented "Snow-Groove" Design

Provides biting edges for excellent snow and ice traction without reducing element stiffness. Enhances the retention of snow in the outer circumferential grooves to capitalize on the higher traction characteristics of snow on snow versus snow on rubber.

Enhanced Studded Performance

A new stud pin hole design improves stud retention and the number has been increased allowing for the use of a greater number of studs for better traction on ice. The stud size is conveniently molded into the sidewall for easy reference.

M+S Rated



S.D.



PSI



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	---------------	---------------	-------------	---------------	----------------------------------	--------------------	-----------------------	-----------	-------

WEATHER-MASTER S/T² white sidewall (.50") size:

WH1-3ET

02601	155/80R13	79S	(4.5) 4.0-5.0	35	963	23.00	6.10	4.10	901	13.0	10.3	12	9-11	14	6.4	M134	
-------	-----------	-----	---------------	----	-----	-------	------	------	-----	------	------	----	------	----	-----	------	--

WEATHER-MASTER S/T² white sidewall (.65") sizes:

W81-3ET

02605	185/75R14	89S	(5.0) 4.5-6.0	35	1279	25.10	7.20	5.00	826	13.5	10.7	12	9-11	18	8.2	V444	
02606	195/75R14	92S	(5.5) 5.0-6.5	35	1389	25.65	7.60	5.20	808	13.5	10.7	12	9-11	19	8.6	V544	
02607	205/75R14	95S	(5.5) 5.0-7.0	35	1521	26.20	7.95	5.60	791	14.0	11.1	13	9-11	21	9.5	V644	
+02608	215/75R14	100S	(6.0) 5.5-7.0	35	1764	26.80	8.40	5.80	774	14.0	11.1	13	9-11	23	10.4	V744	
02614	205/70R14	95S	(6.0) 5.0-7.0	35	1521	25.40	8.05	5.80	816	13.0	10.3	12	9-11	20	9.1	R644	
02615	215/70R14	96S	(6.5) 5.5-7.0	35	1565	25.90	8.50	6.15	801	13.0	10.3	12	9-11	22	10.0	R744	

WEATHER-MASTER S/T² white sidewall (.75") sizes:

WK1-3ET

02609	205/75R15	97S	(5.5) 5.0-7.0	35	1609	27.20	7.95	5.60	762	14.0	11.1	13	9-11	22	10.0	V654	
02610	215/75R15	100S	(6.0) 5.5-7.0	35	1764	27.80	8.40	5.80	746	14.0	11.1	13	9-11	24	10.9	V754	
02611	225/75R15	102S	(6.0) 6.0-7.5	35	1874	28.30	8.70	6.10	733	14.0	11.1	13	9-11	26	11.8	V854	
02612	235/75R15	105S	(6.5) 6.0-8.0	35	2039	28.90	9.10	6.40	717	14.5	11.5	13	9-11	27	12.2	V954	
02616	205/70R15	96S	(6.0) 5.0-7.0	35	1565	26.40	8.00	5.80	785	13.0	10.3	12	9-11	21	9.5	R654	
02617	215/70R15	98S	(6.5) 5.5-7.0	35	1653	26.90	8.40	6.15	771	13.0	10.3	12	9-11	23	10.4	R754	
02618	225/70R15	100S	(6.5) 6.0-7.5	35	1764	27.40	8.70	6.40	757	13.0	10.3	12	9-11	25	11.3	R854	

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability

WEATHER-MASTER S/T²



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	---------------	---------------	-------------	---------------	----------------------------------	--------------------	-----------------------	-----------	-------

WEATHER-MASTER S/T² black sidewall sizes:

W11-3ET

+02625	155/70R13	75S	(4.5) 4.0-5.0	44	853	21.67	5.96	4.95	960	13.0	10.3	12	9-11	14	6.4	R134
02620	175/70R13	82S	(5.0) 4.5-6.0	35	1047	22.90	6.80	5.05	905	13.0	10.3	12	9-11	15	6.8	R334
+02621	185/70R13	86S	(5.5) 4.5-6.0	35	1168	23.45	7.30	5.30	884	13.0	10.3	12	9-11	16	7.3	R434
+02613	175/80R14	88S	(5.0) 4.5-6.0	44	1235	25.01	7.04	5.37	830	13.0	10.3	12	9-11	19	8.6	M344
02622	175/70R14	84S	(5.0) 4.5-6.0	35	1102	23.90	6.80	5.05	867	13.0	10.3	12	9-11	17	7.7	R344
02623	185/70R14	88S	(5.5) 4.5-6.0	35	1235	24.45	7.45	5.30	848	13.0	10.3	12	9-11	18	8.2	R444
02624	195/70R14	91S	(6.0) 5.0-6.5	35	1356	25.00	7.75	5.60	829	13.0	10.3	12	9-11	18	8.2	R544
+02627	165/65R14	79T	(5.0) 4.5-6.0	44	963	22.39	6.67	5.25	927	13.0	10.3	12	9-11	19	8.6	F244
02641	175/65R14	82T	(5.0) 5.0-6.0	44	1047	23.10	6.85	5.20	898	13.0	10.3	12	9-11	16	7.3	F344
02642	185/65R14	86T	(5.5) 5.0-6.5	44	1168	23.55	7.35	5.57	880	13.0	10.3	12	9-11	17	7.7	F444
+02643	195/65R14	89T	(6.0) 5.5-7.0	44	1279	24.00	7.85	5.95	864	13.0	10.3	12	9-11	18	8.2	F544
+02631	185/60R14	82T	(5.5) 5.0-6.5	44	1047	22.85	7.30	5.70	907	13.0	10.3	12	9-11	18	8.2	E444
02632	195/60R14	86T	(6.0) 5.5-7.0	44	1168	23.30	7.82	6.05	890	13.0	10.3	12	9-11	19	8.6	E544
02651	185/65R15	88T	(5.5) 5.0-6.5	44	1235	24.51	7.55	5.77	846	13.0	10.3	12	9-11	19	8.6	F454
02652	195/65R15	91T	(6.0) 5.5-7.0	44	1356	25.00	7.85	6.09	829	13.0	10.3	12	9-11	20	9.1	F554
02629	195/65R15RE	95T	(6.0) 5.5-7.0	50	1521	25.00	7.85	6.09	829	13.0	10.3	12	9-11	22	10.0	F556
02653	205/65R15	94T	(6.0) 5.5-7.5	44	1477	25.45	8.02	6.05	815	13.0	10.3	12	9-11	22	10.0	F654
02630	205/65R15RE	99T	(6.0) 5.5-7.5	50	1709	25.45	8.02	6.05	815	13.0	10.3	12	9-11	23	10.4	F656
02654	215/65R15	96T	(6.5) 6.0-7.5	44	1565	25.98	8.55	6.50	798	13.0	10.3	12	9-11	24	10.9	F754
02634	185/60R15	84T	(5.5) 5.0-6.5	44	1102	23.88	7.44	5.75	871	13.0	10.3	12	9-11	19	8.6	E454
02635	195/60R15	88T	(6.0) 5.5-7.0	44	1235	24.30	7.80	6.05	853	13.0	10.3	12	9-11	21	9.5	E554
02636	205/60R15	91T	(6.0) 5.5-7.5	44	1356	24.75	8.15	6.35	838	13.0	10.3	12	9-11	22	10.0	E654
02637	215/60R15	94T	(6.5) 6.0-7.5	44	1477	25.21	8.60	6.70	822	13.0	10.3	12	9-11	23	10.4	E754
+02663	185/55R15	82T	(6.0) 5.0-6.5	44	1047	23.28	7.57	6.14	893	13.0	10.3	12	9-11	19	8.6	G454
02664	195/55R15	85T	(6.0) 5.5-7.0	44	1135	23.75	7.91	6.13	876	13.0	10.3	12	9-11	20	9.1	G554
02665	205/55R15	88T	(6.5) 5.5-7.5	44	1235	24.14	8.38	6.68	861	13.0	10.3	12	9-11	21	9.5	G654
02646	205/65R16	95T	(6.0) 5.5-7.5	44	1521	26.45	8.02	6.20	790	13.0	10.3	12	9-11	23	10.4	F664
02655	215/65R16	98T	(6.5) 6.0-7.5	44	1653	26.98	8.55	6.50	768	13.0	10.3	12	9-11	26	11.8	F764
*02648	235/65R16	103T	(7.0) 6.5-8.5	44	1929	27.94	9.56	7.37	742	13.0	10.3	12	9-11	27	12.2	F964
02660	205/60R16	92T	(6.0) 5.5-7.5	44	1389	25.77	8.33	6.48	807	13.0	10.3	12	9-11	23	10.4	E664
02639	215/60R16	95T	(6.5) 6.0-7.5	44	1521	26.15	8.50	6.50	793	13.0	10.3	12	9-11	24	10.9	E764
02640	225/60R16	98T	(6.5) 6.0-8.0	44	1653	26.57	8.75	6.70	780	13.0	10.3	12	9-11	25	11.3	E864
02644	235/60R16	100T	(7.0) 6.5-8.5	44	1764	26.96	9.45	7.28	771	13.0	10.3	12	9-11	28	12.7	E964
02661	205/55R16	91T	(6.5) 5.5-7.5	44	1356	24.80	8.35	7.00	836	13.0	10.3	12	9-11	23	10.4	G664
02662	215/55R16RE	97T	(7.0) 6.0-7.5	44	1609	25.35	8.90	7.39	819	13.0	10.3	12	9-11	25	11.3	G766
02667	205/50R16	87T	(6.5) 5.5-7.5	44	1201	24.27	8.34	6.96	856	13.0	10.3	12	9-11	21	9.5	H664
02668	225/50R16	92T	(7.0) 6.0-8.0	44	1389	25.10	9.17	7.89	827	13.0	10.3	12	9-11	25	11.3	H864
*02647	215/65R17	99T	(6.5) 6.0-7.5	44	1709	27.72	9.14	6.78	751	13.0	10.3	12	9-11	28	12.7	F774
*02628	215/60R17	96T	(6.5) 6.0-7.5	44	1565	27.24	9.03	6.96	762	13.0	10.3	12	9-11	26	11.8	E774
*02633	225/60R17	99T	(6.5) 6.0-8.0	44	1709	27.72	9.14	7.18	751	13.0	10.3	12	9-11	28	12.7	E874
*02649	215/55R17	94T	(7.0) 6.0-7.5	44	1477	26.36	9.46	7.39	789	13.0	10.3	12	9-11	26	11.8	G774
02675	225/55R17	97T	(7.0) 6.0-8.0	44	1609	26.88	9.20	7.49	774	13.0	10.3	12	9-11	28	12.7	G874
02676	235/55R17	99T	(7.5) 6.5-8.5	44	1709	27.22	9.79	7.83	764	13.0	10.3	12	9-11	31	14.1	G974
02666	215/50R17	91T	(7.0) 6.0-7.5	44	1356	25.69	8.82	7.35	808	13.0	10.3	12	9-11	25	11.3	H774
02669	225/45R17RE	94T	(7.5) 7.0-8.5	50	1477	25.09	9.03	7.78	828	13.0	10.3	12	9-11	27	12.2	J876
02670	235/45R17	94T	(8.0) 7.5-9.0	44	1477	25.53	9.30	8.17	814	13.0	10.3	12	9-11	28	12.7	J974
*02645	225/60R18	100T	(6.5) 6.0-8.0	44	1764	26.57	8.75	7.18	780	13.0	10.3	12	9-11	24	10.9	E884

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability

* New Sizes - Winter '07-08

